

Chinese Wood Oil

General

Chinese wood oil or tung oil is extracted from the seeds of the tung tree. Thanks to its extremely small molecules, the oil has excellent depth penetration properties and has long been used to protect wood against moisture penetration and cracking. It is also suitable for treating hardwoods such as teak and mahogany. The oil is combined with linseed oil and solvent.

Areas of application

For all types of wood – Garden furniture, Terraces, Windows, Doors, Boats. Can be used both indoors and out.

Instructions for use

The surface must be dry and clean. Highly absorbent surfaces should be coated until saturated. Any excess oil should be wiped off with a rag. NB! Soaked rags, cotton waste, etc. can self-ignite and so should be soaked in water and discarded in a fireproof location. Do not treat outdoor wood too early in spring, as it is best to allow the sun to dry out the timber.

Technical data

Colour:	pale yellow
Dry content:	45- volume%
Density:	830 kg/m ³
Solvent:	low-aromatic white spirit
Drying time:	16-24 hours, depending on temperature and humidity
Flash point:	40 °C
Coverage:	1 litre treats approx. 4-10 m ² depending on the dryness of the wood
Cleaning and dilution:	low-aromatic white spirit

Utgåva: 070312

Dessa anvisningar och information är avsedda att vägleda förbrukaren vid användning av produkten och lämnas utan förbindelse. Vid oklarhet tillråds egna prov eller skriftliga råd från oss.
