

Noxudol Body Stone Protection

Stone-protecting device

General

Noxudol Body Stone Protection is a fast drying, gum- and alkyd-based rust protecting compound with very good adhesion.

Range of application

The product is especially suitable for visible parts, i.e. front-panels and door sill boxes as well as primer for the treatment of damage caused by flying stones and similar minor rust damages. **Noxudol Body Stone Protection** gives a tarnish which can be left as it is or be painted over.

Instructions for use

Make sure that the surface is dry and free from oil, dirt and rust. Prime bare steel surfaces before application. Mask and cover all parts that are not going to be sprayed. Protect the floor. Shake the bottle vigorously for 1 minute and apply a thin and even layer from a distance of 25-30cm at a temperature of min. 15°C. To avoid clogging of the spray tip after use – turn the tin upside down and spray for some seconds until only gas escapes through the valve.

Technical data

Type of product:	alkyd resin/polymer
Solvent:	mixture of aromatic and non aromatic white spirit
Colour:	black
Consistency:	thick liquid-sprayable
Thinner:	white spirit
Clean up:	white spirit
Chemical resistance:	resistant to road salt and other chemicals frequently found on the roads. Resistant to degreasing agents.
Temperature resistance:	up to +100 °C
Storing instructions:	store in a cool place
Recommended film thickness:	100-250 µm

Issue: 040505 Replaces: 930111

These information are for guidance only and are given without obligation. If there is some confusion we recommend that you do your own tests and ask for advice in writing from us.
